

TEKNOFLOR®

HIGH PERFORMANCE FLOORING




NO WAX
NO BUFF
EASY TO
CLEAN

MOONSCAPES HPD™
COMMERCIAL RESILIENT SHEET FLOORING

OUT-OF-THIS-WORLD PERFORMANCE.

Teknoflor® Moonscapes HPD™ Collection, a non-directional resilient sheet, is one of the most durable and maintenance-free surfaces in the market today. This collection makes it easy to coordinate your floor options with fabrics, wall coverings and furniture in hospitals, nursing homes, offices and hospitality settings. For more information, contact your Teknoflor sales representative.



DURABLE AND LOW
MAINTENANCE

ENVIRONMENTALLY
FRIENDLY

SAFE

OVERALL THICKNESS

WARRANTY

APPLICATIONS

- **No Wax, No Buff** and no sealers or finishes needed; easily cleaned by damp mopping or auto-scrubbing
- Thicker 2.3mm gauge for enhanced performance in heavy traffic areas
- Maintenance savings result in investment payback in approximately two years
- Antimicrobial agent incorporated into the wear layer which effectively inhibits bacterial growth on the flooring surface
- No buff floors mean no bacteria, dust or wax particles are thrown into the air during cleaning
- No odors from floor finishes or strippers; no wax flushed into sewer system
- Made with 100% Virgin Vinyl
- ADA Compliant
- Meets fire test standards and is suitable for use in emergency exits and corridors
- 2.3mm (0.090")
- 12-year commercial warranty
- Ideal for Healthcare, Senior Living, Retail, Corporate/Office, Academic and Hospitality Environments



8604 Bianco Romano



8612 Creme Bahia



8639 Baltic Brown



8642 Pearl Gray



8652 Juparana Taupe



8653 Tan Baja



8654 Ikon Tan



8658 Ayes Green



8661 Kashmere Creme

TEKNOFLOR® MOONSCAPES HPD™

COMMERCIAL RESILIENT SHEET

PRODUCT DATA	
STANDARD SPECIFICATION	ASTM F1303
CLASSIFICATION	Type I Grade 1
BACKING CLASS	Class A 4-Ply fused backing system comprised of PVC Layer, Fiberglass, PVC internal layer and PVC backing layer
DIMENSIONS	6' Wide x 75' Long
ROLL SIZE	50 Square Yards (275 lbs. per roll)
WEIGHT	5.5 lbs. per Square Yard
OVERALL THICKNESS	2.3 mm (0.090")
WEAR LAYER THICKNESS	20 mils
PATTERN REPEAT	72"w x 29.94"L (No Pattern Match is required)
WARRANTY	12-Year

SAFETY & PERFORMANCE	TEST METHOD	STANDARD REQUIREMENT	RESULT
CHEMICAL RESISTANCE	ASTM F925	0- No change or 1 - Slight Change	Exceeds requirements
HEAT STABILITY COLOR CHANGE	ASTM F1514	$\Delta E < 8.0$ avg. @7 days	Passes
LIGHT STABILITY COLOR CHANGE	ASTM F1515	$\Delta E < 8.0$ avg. @300 hrs.	Passes
STATIC LOAD LIMIT	ASTM F970	250 psi \leq 0.005" Residual Indentation	Exceeds Requirements 1,000 psi at maximum limit
FLOORSCORE	Certified		Certification # SCS-FS-04567
ABRASION RESISTANCE	ASTM D4060	H18 Wheel & 1 kg mass applied	19,000 Cycles until design layer visibly affected
STATIC COEFFICIENT OF FRICTION (SCOF)	D2047	≥ 0.5 SCOF Dry	≥ 0.6 SCOF Dry
CRITICAL RADIANT FLUX	E648	Class I: ≥ 0.45 w/cm ² Class II: ≥ 0.22 w/cm ²	Class I
SMOKE GENERATION	E662	<450 Flaming & Non-Flaming	<450 Flaming & Non-Flaming
APPROVED FOR EMERGENCY EGRESS AREAS - NFPA 101			



Schedule
GS-27F-0504H • GS-27F-0036V
GS-27F-0015V

