



TEKNOFLOR®

NATURESCAPES HPD™ INSTALLATION (

Revised Novem

Before proceeding, visit www.teknoflor.com to obtain and review the current installation guide, maintenance and other relevant documentation. This installation guide covers Teknoflor® Naturescapes HPD™ sheet flooring. Failure to follow the current installation guidelines and other applicable technical documents may result in unintended installation issues and void the product warranty.

MATERIAL RECEIVING, STORAGE & HANDLING

- Upon receipt, immediately remove all shrink wrap from pallet(s) and confirm materials are the correct color and quantity for each dye lot with consecutive roll numbers for sheet goods. Carefully check all materials for damage. Note any damage on bill of lading when signing for delivery. Visible damage not reported on bill of lading is the trucking company's responsibility.
- Immediately report discrepancies to Teknoflor® Customer Service at (800) 522-9166.
- Store all flooring products and accessories in a dry interior area maintained between 65°F and 85°F (18°C and 29°C). Using outside temporary storage and other uncontrolled storage locations may result in unintended installation issues including bond failure, gapping or buckling and is not covered under the Teknoflor® Naturescapes HPD™ Warranty.
- Handle materials with care to prevent unintended damage.
- SHEET FLOORING - Once received, unstrap all rolls from pallet and store upright within 24 hours. This helps prevent moisture distortion and compression.

JOBSITE EVALUATION & PREPARATION

Proper jobsite evaluation and subfloor preparation are key to the successful installation of Teknoflor® flooring products without performing a thorough subfloor preparation is not rectified. Refer to the current ASTM F710 "Standard Practice for Testing and Evaluating Concrete Subflooring as well as current relevant American Concrete Institute (www.concrete.org). All subfloors must be tested for moisture content. It is strongly advised to have moisture testing conducted by an independent certified contractor.

JOBSITE CONDITIONS AND TESTING MUST BE PROPERLY EVALUATED AND CONFIRM PROJECT MEETS ALL PRODUCT AND ADHESIVE REQUIREMENTS BEFORE PROCEEDING. IN ORDER TO FILE A CLAIM, COMPLETE PROJECT DOCUMENTATION, ISSUE AND SAMPLES OF DEFECT ARE REQUIRED. FAILURE TO FOLLOW THESE INSTRUCTIONS WILL VOID WARRANTY.

ALL WARRANTIES AND GUARANTEES PERTAINING TO THE INSTALLATION OF TEKNOFLOR® FLOORING PRODUCTS RESTS SOLELY WITH THE GENERAL CONTRACTOR AND NOT WITH TEKNOFLOR®.

ALL PERFORMANCE RELATED ISSUES ARISING FROM THE USE OF UNRECOMMENDED PREPARATION MATERIALS, MOISTURE MITIGATION SYSTEMS, ADHESIVES AND ANCHORING PRODUCTS OR METHODS ARE THE SOLE AND EXCLUSIVE RESPONSIBILITY OF EACH MANUFACTURER AND/OR THE FLOORING AND GENERAL CONTRACTOR OR PARTY WHO APPROVES

We've made updates!



Here are 3 ways to keep work flowing in Dropbox.

[Skip](#)

[Show me](#)